KOLKATA PORT TRUST कोलकाता पत्तन न्यास KOLKATA - FEBRUARY 2018

H.M.(R)'S OFFICE **DATED** :26.12.2017

FSTIMATE	D FRESH WA	TER DRAFT F	ORECAST			Y 2018 DATED :26.12.2017 018 FOR KOLKATA (Lighted channel draft)
INWARD Date		10.5kts&Ovr	Over9kts	Over7.5kts	Embk time	N O T E S
1st	7.1	6.9	6.7	6.5	311830	14 0 1 2 0
2nd	7.1	7.0	6.8	6.6	011915	Vessels report their ETA to Pilot station at least
3rd	7.1	6.9	6.7	6.5	022000	24 hrs. in advance SSB 4147.4 and 8295.4 KHz.
4th	6.9	6.7	6.5	6.3	032030	24 ms. in advance oob 4147.4 and 6255.4 mmz.
5th	6.6	6.4	6.2	6.0	042100	2. Pilot embarkation time at Middleton Channel contact
6th	6.0	5.8	5.6	5.4	052145	pilot station on Channel 16/68.
7th	5.5	5.3	5.1	4.9	062215	phot station on charmer 10/00.
8th	5.0	4.8	4.6	4.4	072245	Vessels should anchor southward of Eastern Channel
*9th	4.9	4.7	4.5	4.3	081100	Light Vessel (21*04'N,88*11'12.5E) on arrival sandheads.
10th	5.3	5.1	4.9	4.7	091200	Light vesser (21 0410,00 11 12.3L) on anival sandicaes.
11th	5.4	5.2	5.0	4.8	101400	4. VTMS assistance is available above 21*25' on VHF
12th	5.6	5.4	5.2	5.0	111530	channel 16/68 from control station Haldia (22*02'N 88*06'E).
13th	5.9	5.7	5.5	5.3	121645	onamic 10/00 from ocitico ciation fiana (22 02 14 00 00 2).
14th	6.1	5.9	5.7	5.5	131730	5. Outward deep drafts apply to vessels brought to BB
15th	6.4	6.2	6.0	5.8	141800	anchorages on the previous day tide.
16th	6.6	6.4	6.2	6.0	151845	anonorages on the provious day tide.
17th	6.8	6.6	6.4	6.2	161900	6. One light drafted fast ship can avail of dockhead sailing
18th	6.9	6.7	6.5	6.3	171930	on certain dates. Please refer Notice Oct'99.
19th	6.9	6.7	6.5	6.3	182000	5 55.12 34.05. 1 104.05 10101 1101100 00100.
20th	6.9	6.7	6.5	6.3	192030	7. Drafts are subject to adjustment.
21st	6.8	6.6	6.4	6.2	202100	2.5.6 are outspool to adjustment.
22nd	6.2	6.0	5.8	5.6	212145	8. IT IS COMPULSORY FOR MASTERS TO PROCURE
23rd	5.4	5.2	5.0	4.8	222215	ESTUARY RIVER CHARTS THROUGH THEIR AGENTS FOR
*24th	4.9	4.7	4.5	4.3	231045	THE SAFETY OF THEIR VESSELS.
25th	5.7	5.5	5.3	5.1	241145	1112 0/W 211 01 1112 W V200220.
26th	5.8	5.6	5.4	5.2	251315	9. E.Gut-2.5mtrs. and Moyapur - 3.6mtrs.
27th	6.2	6.0	5.8	5.6	261500	or and mayapar crommer
28th	6.6	6.4	6.2	6.0	271630	10. IF ANY PROJECTED PARAMETERS ARE CHANGED,
	0.0		0.2	0.0		DRAFTS LIKELY TO BE ADJUSTED ACCORDINGLY.
OUTWARD						
1st	6.4	6.2	6.0	5.8		11. Vessel required to have 0.2mtrs. trim aft between DH & GR.
2nd	6.4	6.2	6.0	5.8		'
3rd	6.3	6.1	5.9	5.7		12.* TO AVAIL MAXIMUM DRAFT OF THE DAY VESSEL BOUND
4th	6.1	5.9	5.7	5.5		DH & BB AND KOLKATA MUST PICK UP BY EMBARKATION
5th	6.0	5.8	5.6	5.4		TIME. THEY CAN ONLY ENTER ON TWO TIDES.
6th	5.9	5.7	5.5	5.3		
7th	5.7	5.5	5.3	5.1		
8th	5.6					13. BOTH INWARD AND OUTWARD DRAFTS ARE SUBJECT
9th		5.4	5.2	5.0		13. BOTH INWARD AND OUTWARD DRAFTS ARE SUBJECT TO ALL LIGHTS IN ORDER.
	5.3	5.4 5.1	5.2 4.9	5.0 4.7		
*10th						
	5.3	5.1	4.9	4.7		TO ALL LIGHTS IN ORDER.
*10th 11th 12th	5.3 4.9 5.1 5.4	5.1 4.7 4.9 5.2	4.9 4.5 4.7 5.0	4.7 4.3 4.5 4.8		TO ALL LIGHTS IN ORDER. 14. For Kolkata/BB Vessels above LOA 165mtrs. the
*10th 11th	5.3 4.9 5.1	5.1 4.7 4.9 5.2 5.4	4.9 4.5 4.7	4.7 4.3 4.5		TO ALL LIGHTS IN ORDER. 14. For Kolkata/BB Vessels above LOA 165mtrs. the
*10th 11th 12th	5.3 4.9 5.1 5.4 5.6 5.7	5.1 4.7 4.9 5.2	4.9 4.5 4.7 5.0 5.2 5.3	4.7 4.3 4.5 4.8		TO ALL LIGHTS IN ORDER. 14. For Kolkata/BB Vessels above LOA 165mtrs. the permissible draft will be 0.2mtrs. less than the predicted draft.
*10th 11th 12th 13th 14th 15th	5.3 4.9 5.1 5.4 5.6 5.7 5.9	5.1 4.7 4.9 5.2 5.4 5.5 5.7	4.9 4.5 4.7 5.0 5.2 5.3 5.5	4.7 4.3 4.5 4.8 5.0 5.1 5.3		TO ALL LIGHTS IN ORDER. 14. For Kolkata/BB Vessels above LOA 165mtrs. the permissible draft will be 0.2mtrs. less than the predicted draft. 15. All vessels are required to have two serviceable
*10th 11th 12th 13th 14th	5.3 4.9 5.1 5.4 5.6 5.7	5.1 4.7 4.9 5.2 5.4 5.5	4.9 4.5 4.7 5.0 5.2 5.3	4.7 4.3 4.5 4.8 5.0 5.1		TO ALL LIGHTS IN ORDER. 14. For Kolkata/BB Vessels above LOA 165mtrs. the permissible draft will be 0.2mtrs. less than the predicted draft. 15. All vessels are required to have two serviceable
*10th 11th 12th 13th 14th 15th	5.3 4.9 5.1 5.4 5.6 5.7 5.9 6.1 6.2	5.1 4.7 4.9 5.2 5.4 5.5 5.7	4.9 4.5 4.7 5.0 5.2 5.3 5.5	4.7 4.3 4.5 4.8 5.0 5.1 5.3 5.5 5.6		TO ALL LIGHTS IN ORDER. 14. For Kolkata/BB Vessels above LOA 165mtrs. the permissible draft will be 0.2mtrs. less than the predicted draft. 15. All vessels are required to have two serviceable bower anchors for safe transit.
*10th 11th 12th 13th 14th 15th 16th 17th 18th	5.3 4.9 5.1 5.4 5.6 5.7 5.9 6.1 6.2 6.2	5.1 4.7 4.9 5.2 5.4 5.5 5.7 5.9	4.9 4.5 4.7 5.0 5.2 5.3 5.5 5.7	4.7 4.3 4.5 4.8 5.0 5.1 5.3 5.5		TO ALL LIGHTS IN ORDER. 14. For Kolkata/BB Vessels above LOA 165mtrs. the permissible draft will be 0.2mtrs. less than the predicted draft. 15. All vessels are required to have two serviceable bower anchors for safe transit.
*10th 11th 12th 13th 14th 15th 16th 17th 18th 19th	5.3 4.9 5.1 5.4 5.6 5.7 5.9 6.1 6.2 6.2	5.1 4.7 4.9 5.2 5.4 5.5 5.7 5.9 6.0	4.9 4.5 4.7 5.0 5.2 5.3 5.5 5.7 5.8 5.8	4.7 4.3 4.5 4.8 5.0 5.1 5.3 5.5 5.6		TO ALL LIGHTS IN ORDER. 14. For Kolkata/BB Vessels above LOA 165mtrs. the permissible draft will be 0.2mtrs. less than the predicted draft. 15. All vessels are required to have two serviceable bower anchors for safe transit.
*10th 11th 12th 13th 14th 15th 16th 17th 18th	5.3 4.9 5.1 5.4 5.6 5.7 5.9 6.1 6.2 6.2	5.1 4.7 4.9 5.2 5.4 5.5 5.7 5.9 6.0 6.0	4.9 4.5 4.7 5.0 5.2 5.3 5.5 5.7 5.8 5.8 5.8	4.7 4.3 4.5 4.8 5.0 5.1 5.3 5.5 5.6 5.6 5.6		TO ALL LIGHTS IN ORDER. 14. For Kolkata/BB Vessels above LOA 165mtrs. the permissible draft will be 0.2mtrs. less than the predicted draft. 15. All vessels are required to have two serviceable bower anchors for safe transit.
*10th 11th 12th 13th 14th 15th 16th 17th 18th 19th	5.3 4.9 5.1 5.4 5.6 5.7 5.9 6.1 6.2 6.2	5.1 4.7 4.9 5.2 5.4 5.5 5.7 5.9 6.0 6.0	4.9 4.5 4.7 5.0 5.2 5.3 5.5 5.7 5.8 5.8	4.7 4.3 4.5 4.8 5.0 5.1 5.3 5.5 5.6 5.6 5.6 5.6 5.5		TO ALL LIGHTS IN ORDER. 14. For Kolkata/BB Vessels above LOA 165mtrs. the permissible draft will be 0.2mtrs. less than the predicted draft. 15. All vessels are required to have two serviceable bower anchors for safe transit.
*10th 11th 12th 13th 14th 15th 16th 17th 18th 19th 20th	5.3 4.9 5.1 5.4 5.6 5.7 5.9 6.1 6.2 6.2 6.2	5.1 4.7 4.9 5.2 5.4 5.5 5.7 5.9 6.0 6.0 6.0	4.9 4.5 4.7 5.0 5.2 5.3 5.5 5.7 5.8 5.8 5.8	4.7 4.3 4.5 4.8 5.0 5.1 5.3 5.5 5.6 5.6 5.6 5.6 5.5 5.5		TO ALL LIGHTS IN ORDER. 14. For Kolkata/BB Vessels above LOA 165mtrs. the permissible draft will be 0.2mtrs. less than the predicted draft. 15. All vessels are required to have two serviceable bower anchors for safe transit.
*10th 11th 12th 13th 14th 15th 16th 17th 18th 19th 20th 21st	5.3 4.9 5.1 5.4 5.6 5.7 5.9 6.1 6.2 6.2 6.2 6.2	5.1 4.7 4.9 5.2 5.4 5.5 5.7 5.9 6.0 6.0 6.0 6.0 5.9	4.9 4.5 4.7 5.0 5.2 5.3 5.5 5.7 5.8 5.8 5.8 5.7	4.7 4.3 4.5 4.8 5.0 5.1 5.3 5.5 5.6 5.6 5.6 5.6 5.5		TO ALL LIGHTS IN ORDER. 14. For Kolkata/BB Vessels above LOA 165mtrs. the permissible draft will be 0.2mtrs. less than the predicted draft. 15. All vessels are required to have two serviceable bower anchors for safe transit.
*10th 11th 12th 13th 14th 15th 16th 17th 18th 19th 20th 21st 22nd 23rd 24th	5.3 4.9 5.1 5.4 5.6 5.7 5.9 6.1 6.2 6.2 6.2 6.2 6.1 6.1	5.1 4.7 4.9 5.2 5.4 5.5 5.7 5.9 6.0 6.0 6.0 6.0 5.9 5.9	4.9 4.5 4.7 5.0 5.2 5.3 5.5 5.7 5.8 5.8 5.8 5.7 5.7	4.7 4.3 4.5 4.8 5.0 5.1 5.3 5.5 5.6 5.6 5.6 5.6 5.5 5.5		TO ALL LIGHTS IN ORDER. 14. For Kolkata/BB Vessels above LOA 165mtrs. the permissible draft will be 0.2mtrs. less than the predicted draft. 15. All vessels are required to have two serviceable bower anchors for safe transit.
*10th 11th 12th 13th 14th 15th 16th 17th 18th 19th 20th 21st 22nd 23rd	5.3 4.9 5.1 5.4 5.6 5.7 5.9 6.1 6.2 6.2 6.2 6.1 6.1 6.0	5.1 4.7 4.9 5.2 5.4 5.5 5.7 5.9 6.0 6.0 6.0 6.0 5.9 5.9	4.9 4.5 4.7 5.0 5.2 5.3 5.5 5.7 5.8 5.8 5.8 5.7 5.7 5.6	4.7 4.3 4.5 4.8 5.0 5.1 5.3 5.5 5.6 5.6 5.6 5.6 5.5 5.5 5.5		TO ALL LIGHTS IN ORDER. 14. For Kolkata/BB Vessels above LOA 165mtrs. the permissible draft will be 0.2mtrs. less than the predicted draft. 15. All vessels are required to have two serviceable bower anchors for safe transit.
*10th 11th 12th 13th 14th 15th 16th 17th 18th 19th 20th 21st 22nd 23rd 24th *25th	5.3 4.9 5.1 5.4 5.6 5.7 5.9 6.1 6.2 6.2 6.2 6.2 6.1 6.0 5.9 4.9	5.1 4.7 4.9 5.2 5.4 5.5 5.7 5.9 6.0 6.0 6.0 6.0 5.9 5.9 5.8 5.7 4.7	4.9 4.5 4.7 5.0 5.2 5.3 5.5 5.7 5.8 5.8 5.8 5.7 5.6 5.7 5.6 5.5	4.7 4.3 4.5 4.8 5.0 5.1 5.3 5.5 5.6 5.6 5.6 5.6 5.5 5.5 5.5		TO ALL LIGHTS IN ORDER. 14. For Kolkata/BB Vessels above LOA 165mtrs. the permissible draft will be 0.2mtrs. less than the predicted draft. 15. All vessels are required to have two serviceable bower anchors for safe transit. 16. All vessels A.I.S. Pilot plug required to be operational. Sd/- HARBOUR MASTER(RIVER)
*10th 11th 12th 13th 14th 15th 16th 17th 18th 19th 20th 21st 22nd 23rd 24th *25th	5.3 4.9 5.1 5.4 5.6 5.7 5.9 6.1 6.2 6.2 6.2 6.1 6.1 6.0 5.9 4.9	5.1 4.7 4.9 5.2 5.4 5.5 5.7 5.9 6.0 6.0 6.0 6.0 5.9 5.9 5.8 5.7	4.9 4.5 4.7 5.0 5.2 5.3 5.5 5.7 5.8 5.8 5.8 5.7 5.6 5.7 5.6 5.5	4.7 4.3 4.5 4.8 5.0 5.1 5.3 5.5 5.6 5.6 5.6 5.5 5.5 5.5 5.5		TO ALL LIGHTS IN ORDER. 14. For Kolkata/BB Vessels above LOA 165mtrs. the permissible draft will be 0.2mtrs. less than the predicted draft. 15. All vessels are required to have two serviceable bower anchors for safe transit. 16. All vessels A.I.S. Pilot plug required to be operational. Sd/-
*10th 11th 12th 13th 14th 15th 16th 17th 18th 19th 20th 21st 22nd 23rd 24th *25th	5.3 4.9 5.1 5.4 5.6 5.7 5.9 6.1 6.2 6.2 6.2 6.2 6.1 6.0 5.9 4.9	5.1 4.7 4.9 5.2 5.4 5.5 5.7 5.9 6.0 6.0 6.0 6.0 5.9 5.9 5.8 5.7 4.7	4.9 4.5 4.7 5.0 5.2 5.3 5.5 5.7 5.8 5.8 5.8 5.7 5.6 5.7 5.6 5.5	4.7 4.3 4.5 4.8 5.0 5.1 5.3 5.5 5.6 5.6 5.6 5.6 5.5 5.5 5.5		TO ALL LIGHTS IN ORDER. 14. For Kolkata/BB Vessels above LOA 165mtrs. the permissible draft will be 0.2mtrs. less than the predicted draft. 15. All vessels are required to have two serviceable bower anchors for safe transit. 16. All vessels A.I.S. Pilot plug required to be operational. Sd/- HARBOUR MASTER(RIVER)